

EVACUATED INTEGRATED



Solar  Z

THE LATEST
TECHNOLOGY



SOLAROZ LOW PRESSURE SYSTEM



HIGH FRAMES ALSO AVAILABLE





MODEL	TUBES	CAPACITY	WEIGHT DRY	FOOT PRINT cm
SSZ 47/1500-24	24 47x1500mm	200 LITRES	88kg	183L x 178w
SSZ 58/1800-30	30 58x1800mm	300 LITRES	112kg	220L x 249w

SERIOUS HOT WATER



SSZ series

Inner tank	Stainless 316 [.5mm]
Insulation layer	Polyurethane foam 55mm
Outer tank	Stainless 304-2B [0.4mm]
Frame	Stainless 304 [1.2mm]
Evacuated tube	Borosilicate Glass 2mm
Tube type	3 target
Heating Element	2 kw



FEATURES

- 1) Unpressurized tank, Stainless steel.
- 2) Reliable and efficient evacuated tubes.
- 3) Wet back option.
- 4) Easy installation tank only weighs 40kgs.
- 5) Maintenance free.
- 6) Stable solar conversion during the day.
- 7) No pump or controller needed.
- 8) Frost tolerant tested to -20c



SOLAR0Z STC VALUES

	Zone 1	Zone 2	Zone 3	Zone 4





SERIOUS HOT WATER

